REGENCY CLASSIC™ F2450

Medium Non-Catalytic Wood Stove



F2450 shown with black classic door, bottom heat shield, black legs and rear heat deflector

This Regency Classic medium wood stove provides the perfect amount of heat for most spaces. Load wood in this stove front to back or side to side for the optimum convenience.

FEATURES

- Large fire viewing area, with heat radiating ceramic glass
- Wood-finished handle
- Heavy-duty cast hinges that will never bend or break
- Solid forged steel adjustable cam lock ensures a tight door seal over time
- Front-mounted air adjustment
- Air operating safety tool
- High-performance brick-lined firebox reflects heat
- Non-obtrusive air wash curtain keeps glass clean
- Welded ash lip will never bend or break
- Rear heat deflector allowing for closer clearances
- Mobile home and alcove approved

OPTIONS

- Cast iron door with heat radiating ceramic glass in black or nickel accent
- Pedestal base
- Wood storage pedestal
- Bottom heat shield with cast iron legs in black or brushed nickel
- Ash drawer
- 2-speed blower
- Convector airmate
- Outside air kit
- Mobile home kit
- Wood venting

SPECIFICATIONS	
Maximum BTU*	75,000
Typical sq. ft. heated**	1,000 - 2,200
EPA Efficiency	72% LHV / 67% HHV
Max log size	18"
Burn time	Up to 10 hours
Emissions	1.4 g/h
Firebox size	2.3 cu. ft.
Flue size	6"

* Length of burn time and BTU range depend on type of wood, moisture content, climate conditions and installation. Refer to page 15 for BTU calculation method.
** Varies depending on home floor plan, house layout, heat loss of the house and quality/moisture content of wood.